



GLAZING VISION

Manual Skyhatch Skylight

407-TDS-US-001 – v1.3 – 26 Aug 2020

Name: Manual Skyhatch

Type: Manually operated hinged skylight

Description:

The Manual Skyhatch is a manually operated product designed to allow infrequent access to a rooftop, such as for maintenance purposes. The lid opens to an angle of approximately 75°, allowing unimpeded access. The lid cannot open to any intermediary positions.

A variety of optional extras such as special color and easy clean coating are available.

This product is robust and long-lasting, boasting excellent thermal performance, air tightness and reliable operation.

Intended Use: Hinged skylight to be used for maintenance access, to provide natural daylight, day-to-day ventilation and weather resistance.

External Weathered Curb Dimensions:

Min Span:	43"	Max Span:	43"
Width:	43", 59" or 79" only		
Min Curb Pitch:	5/8" : 12" (3°)	Max Curb Pitch:	2" : 12" (10°)

Glazing Vision recommends a pitch of at least 1-1/8" : 12" (5°).

Note that the minimum and maximum span, width and pitch are dependent on various factors, your technical sales advisor will be happy to advise on these. Further information on curb requirements and product dimensions can be found on our website or by contacting your technical sales advisor.

Glazing: A wide variety of glazing specifications are available for this product. Your technical sales advisor will be happy to answer any questions regarding specific glass specifications or glazing performance requirements. Otherwise, quotes include suitable and cost effective glazing proposals.

Standard Colors: Qualicoat approved RAL 7015 slate grey outer, RAL 9010 pure white inner.

Manual Operation: The product is opened and closed using two handles mounted on the lid frame. The user is assisted by gas struts and springs mounted within the frame of the product.

Performance and Weathertightness: The product comprises thermally broken aluminum sections consisting of polyamide thermal breaks and closed cell PIR insulation thermally isolating the inner and outer frame sections. Structural integrity is assured through the use of finite element analysis (FEA) and testing.

U-factors are calculated for each product and will be supplied in our quote. Further information and specific performance details can be obtained from your technical sales advisor.

The product is sealed to the curb using silicone and fixed in place with structural fixings which are concealed by a clip-on cover leaving a sleek external finish. Sealing between the base frame and the lid frame is achieved using a combination of silicone bubble and blade seals.

The product has been thoroughly tested.

Security:

This product is designed with security as a priority. The product is secured and locked by a centrally mounted rotating handle, supplied with a key. This mechanically fixes the lid at the two opening corners and cannot be tampered with from the outside.

Optional Extras:

The following optional extras are available for this standard product at additional cost:

- Easy Clean Coating:** A coating applied to the external face of the glass that facilitates water run-off. Helps the glass stay cleaner for longer and makes cleaning easier.
- Special Color(s):** This product has separate inner and outer colors as standard. Each can be swapped for a special color.
- Curb Top Trim:** Cover designed to mask the top of curbs which may be visible through glass when viewed from above. Includes detail to recess standard drywall.

A suite of sales drawings is available.

Custom options may be available upon request but may incur additional design fees – contact your technical sales advisor for more information.

GLAZINGVISION



www.glazingvision.com



833-SKYDOOR (833-759-3667)



sales@glazingvision.com



Technical Data Sheet

Electric skyhatch skylight

407-TDS-US-002 – v1.4 – 12 Dec 2024

Name: Electric Skyhatch

Type: Electrically operated hinged skylight

Description:

The Electric Skyhatch is an electrically operated product designed to allow access to a rooftop, such as for maintenance purposes. The lid opens to an angle of approximately 80°, allowing unimpeded access. A variety of optional extras including a rain sensor, thermostat, remote control and home automation system connectivity are available. This product is robust and long-lasting, boasting excellent thermal performance, air tightness and reliable operation.

Intended Use: Hinged skylight to be used for maintenance access, to provide natural daylight, day-to-day ventilation and weather resistance.

External Weathered Curb Dimensions:	Min Span:	32"	Max Span:	59"
	Min Width:	32"	Max Width:	78"
	Min Area:	6.9 ft ²	Max Area:	23.6 ft ²
	Min Curb Pitch:	5/8" : 12" (3°)	Max Curb Pitch:	12" : 12" (45°)
	<i>Glazing Vision recommends a pitch of at least 1-1/8" : 12" (5°).</i>			

Note that the minimum and maximum span, width and pitch are dependent on various factors, your technical sales advisor will be happy to advise on these. Further information on curb requirements and product dimensions can be found on our website or by contacting your technical sales advisor.

Glazing: A wide variety of glazing specifications are available for this product. Your technical sales advisor will be happy to answer any questions regarding specific glass specifications or glazing performance requirements. Otherwise, quotes include suitable and cost effective glazing proposals.

Standard Colors: Qualicoat approved RAL 7015 slate grey outer, RAL 9010 pure white inner.

Control, Power and Drive: The product is operated using a supplied wall mounted switch connected to a control box mounted inside the product framework via a flying lead.

Also supplied is an externally housed Power Supply Unit requiring connection to the main power supply. It is recommended that the PSU is housed somewhere accessible.

The unit is driven by two scissor linkage mechanisms, mounted on either side creating an uninterrupted view, that are synchronized using motor encoder feedback and, in the event of power failure, can be manually overridden.

Performance and Weathertightness:

The product comprises thermally broken aluminum sections consisting of polyamide thermal breaks and closed cell PIR insulation thermally isolating the inner and outer frame sections. The lid frame of the product employs a dual hardness EPDM insulating gasket to thermally isolate the frame from the interior of the building. Structural integrity is assured through the use of finite element analysis (FEA) and testing.

U-factors are calculated for each product and will be supplied in our quote. Further information and specific performance details can be obtained from your technical sales advisor.

The product is sealed to the curb using silicone and fixed in place with structural fixings which are concealed by a clip-on cover leaving a sleek external finish. The lid seals using a combination of silicone bubble seals and a dual hardness EPDM gasket.

The product has been thoroughly tested.

Security:

This product is designed with security as a priority. The mechanisms cannot be back driven and cannot be tampered with from the outside.

Optional Extras:

The following optional extras are available for this standard product at additional cost:

- Easy Clean Coating:** A coating applied to the external face of the glass that facilitates water run-off. Helps the glass stay cleaner for longer and makes cleaning easier.
- Special Color(s):** This product has separate inner and outer colors as standard. Each can be swapped for a special color.
- Remote Control:** Allows the product to be opened and closed from a short range.
- Rain Sensor:** Automatically closes the product when moisture is detected.
- Rain Sensor Isolator:** An internally mounted wall switch that allows the rain sensor to be turned off so that it does not automatically close the product when moisture is detected.
- Thermostat:** Automatically operates the product to regulate the temperature within the building.
- Keypad or Key Switch:** Offers secure access either via an externally mounted four-digit numerical pass code keypad or a key switch.
- Battery Backup:** Allows full operation of the product for a limited period in the event of a power failure.
- Home Automation:** Allows the product to be operated by contact closure of a third-party home automation system.
- Curb Top Trim:** Cover designed to mask the top of curbs which may be visible through glass when viewed from above. Includes detail to recess standard drywall.

A suite of sales drawings is available.

Custom options may be available upon request but may incur additional design fees – contact your technical sales advisor for more information.